CP PLUS

CP-UNB-CP22M

Apartment Outdoor Station

- HD CMOS camera
- Night vision & Voice indication
- Video & Audio messaging
- Local card opening
- Stainless steel panel, IP54, IK07
- Surface & Flush mounted

System Overview

CP PLUS has introduced a wide range of Video Door-Phones (also known as video door entry or video intercom) which are stand-alone intercom systems that you can use to manage calls made at the entrance to a building (residential complex, detached family home, workplace, etc.) with access controlled by audio visual communication between the inside and outside.

Functions

Hands-free operation

The latest intelligent invention in the field of video door phones is that of the hands-free feature because of which you no longer have to keep the button pushed to talk to a visitor on the phone.

CP-UNB-CP22M
Apartment Outdoor Station

Functions

Electronically controlled door locking

This product by CP Plus enables you to control the opening and locking of your electronically through the system instead of using the outdated key.

High-Resolution Outdoor Unit for Clearer Identification

The product has been integrated with a high-resolution lens that produces clear and vivid details to you for better and accurate identification of the visitors.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.

CP PLUS

CP-UNB-CP22M
Apartment Outdoor Station

Feature	Specification
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
LCD Screen	3" STN 128x64 (7.62cm)
Keypad	Mechanical Button
Reader	Mifare Card
Video Compression	H.264
Image Sensor	1/2.7" 1.3MP CMOS
Lens	4mm
Angle of View	D:95° H:75°
Day/Night	Color Image
Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Door Control	1
Alarm In	2(1ch unlock button, 1ch feedback)
RS485	1
Ethernet	10M/100Mbps
Protocol	TCP/IP
Ingress Protection	IP54 , IK07
Tamper Switch	1
Power	DC 12V

Feature	Specification
Power Consumption	Standby ≤1W, Work ≤10W
Working Temperature	-40°C~+60°C
Relative Humidity	10%~90%RH
Casing	Stainless steel
Dimensions	143.0mm×406.0mm×42.0mm
Weight	1.6Kg