



V-STAR 3+1 Zone Security Panel With GSM Base Auto Dialer (LCD Based Key Pad)

Technical Specification :-



- ✓ Operating Voltage : 220 V AC/ 9-12 V DC
- ✓ Current Consumption of Panel :
- ✓ Quiescent Current : 190 m Amp. Max. (LCD off)
- ✓ Quiescent Current : 240 m Amp. Max. (LCD ON)
- ✓ Operating Current : 320 m Amp. Max.
- ✓ Maximum Load : 3 Amp.
- ✓ Output : Total 3 outputs. 1 for Security, 1 for Fire & 1 for Bell.
- ✓ Response Time : 250 to 750 M. Sec. Programmable
- ✓ Dimension : 11" x 10" 3.5"
- ✓ Case material : ABS resin plastic 1st Grade
- ✓ Mounting : Wall or Flat Surface
- ✓ Color : White

V- STAR

3+1 Zone Security Panel with GSM Base Auto Dialer (LCD Base Key Pad)
Specially Design for Small Establishments
Like Shops, Offices & Flats

Salient & Unique Features of V Star (GSM Based Panel) :-

- Micro controller based system with LCD display for easy installation.
- 3 + 1 Zone Security panel with Inbuilt GSM Auto dialer with LCD & onboard Key Pad.
- Remote programming from any where in the world through phone.
- 3 fully programable zone.
- Zone naming facility available.
- 24 hour 1 separate temper zone in addition of 4 zones.
- Up to 15 numbers of telephone number can be programed for delivering of messages.
- weekly and yearly holiday feature.
- Up to 3 number of keypad can attached.
- Automatic arming and disarming facility available.
- 4 LED indication on display for power, network, battery on & Battery low
- Three different voice messages for 3 different zones.
- Different entry and exit delay for night mode.
- Editable co. banner display on LCD.
- Programmable day & night mode.



- All zones are programmable NO / NC.
 - Operation through Onboard key pad with LCD as well as with phone.
 - 16 key back light key pad.
 - User can operate through SMS as well as by key pad.
 - No. of ring after which panel respond is programmable.
 - Panel can be armed and disarmed through phone.
 - Code can change through remote.
 - Built in battery backup provision.
 - Individual zone status indication on display.
 - Individual entry delay time 1 to 99 min.
 - Individual exit delay time 1 to 99 min.
 - Silent arming.
 - Night mode arming.
 - Non volatile memory.
 - Open zone indication.
 - In built tamper switch.
 - RF arming/disarming and panic. (optional)
 - Inbuilt GSM dialer.
 - Code protected programming.
 - International look.
 - All type of sensor are attachable.
 - One of its kind system with response indicator.
- Very much suitable for small establishments like flats/offices/home/go down. • 4 wire smoke sensor can be attached. • **Extremely true international product at very economic price suit to everybody pocket.**